

**MITANOL S-Force 15W-40 Classic**

Revision date: 09.02.2022

Page 1 of 10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

MITANOL S-Force 15W-40 Classic

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Motor oil multigrade

**Uses advised against**

No information available.

**1.3. Details of the supplier of the safety data sheet**

Company name: MITANOL GmbH  
Street: Industriestraße 8  
Place: D-49577 Ankum  
Telephone: +49 (0)5462/7470-50  
Telefax: +49 (0)5462/7470-33  
e-mail: info@mitanol.de  
Internet: www.mitanol.de  
Responsible Department: Produktsicherheit / Product Safety  
sicherheitsdatenblatt@mitanol.de

**1.4. Emergency telephone****number:** Gifftinformationszentrum Nord (Göttingen)

+49 (0)551/19240

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

**2.2. Label elements****Additional advice on labelling**

According to EC directives or the corresponding national regulations the product does not have to be labelled.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			5,0 - < 7,0 %
	265-158-7	649-468-00-3	01-2119487077-29	
	Asp. Tox. 1; H304			
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified			3,0 - < 5,0 %
	265-159-2	649-469-00-9	01-2119480132-48	
	Asp. Tox. 1; H304			

Full text of H and EUH statements: see section 16.

**MITANOL S-Force 15W-40 Classic**

Revision date: 09.02.2022

Page 2 of 10

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-55-8	265-158-7	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	5,0 - < 7,0 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
64742-56-9	265-159-2	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified	3,0 - < 5,0 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	

**Further Information**

This mixture contains no substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove affected person from the danger area and lay down.  
Do not leave affected person unattended.  
In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**After inhalation**

Remove person to fresh air and keep comfortable for breathing.  
In all cases of doubt, or when symptoms persist, seek medical advice.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap.  
Take off contaminated clothing and wash it before reuse.  
In case of skin irritation, consult a physician.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**After ingestion**

Rinse mouth thoroughly with water.  
Let water be drunk in little sips (dilution effect).  
Do NOT induce vomiting.  
In all cases of doubt, or when symptoms persist, seek medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Use water spray jet to protect personnel and to cool endangered containers.  
Co-ordinate fire-fighting measures to the fire surroundings.  
- Sand  
- Foam.  
- Carbon dioxide (CO<sub>2</sub>).  
- Extinguishing powder  
- In case of major fire and large quantities: Water spray jet, Water mist

**Unsuitable extinguishing media**

Full water jet

**MITANOL S-Force 15W-40 Classic**

Revision date: 09.02.2022

Page 3 of 10

**5.2. Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

In case of fire may be liberated:

- Carbon monoxide (CO)
- Carbon dioxide (CO<sub>2</sub>).
- Nitrogen oxides (NO<sub>x</sub>)
- Sulphur dioxide (SO<sub>2</sub>)
- Phosphorus oxides
- Pyrolysis products, toxic

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. Use of protective clothing

In case of fire and/or explosion do not breathe fumes.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**General measures**

Keep people at a distance and stay on the windward side.

Special danger of slipping by leaking/spilling product.

**For non-emergency personnel**

Wear protective gloves/protective clothing and eye/face protection.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

Prevent spread over a wide area (e.g. by containment or oil barriers).

**6.3. Methods and material for containment and cleaning up**

**For containment**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

Remove from the water surface (e.g. skimming, sucking).

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

Avoid formation of oil dust.

Use personal protection equipment.

Do not put any product-impregnated cleaning rags into your trouser pockets.

Clear spills immediately.

**Advice on protection against fire and explosion**

No special fire protection measures are necessary.

Take precautionary measures against static discharges.

Keep away from sources of ignition - No smoking.

Fire class B

**MITANOL S-Force 15W-40 Classic**

Revision date: 09.02.2022

Page 4 of 10

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed and in a well-ventilated place.  
Keep only in the original container. Store in a cool dry place. (Protect from moisture.)  
Floors should be impervious, resistant to liquids and easy to clean.

**Hints on joint storage**

Do not store together with:  
- Materials capable of ignition under almost all normal temperature conditions  
- Explosives

**Further information on storage conditions**

Temperature control required. Protect from light.

**7.3. Specific end use(s)**

Motor oil multigrade

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			
Worker DNEL, long-term	inhalation	systemic		2,73 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local		5,58 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic		0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local		1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic		0,74 mg/kg bw/day
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified			
Worker DNEL, long-term	inhalation	systemic		2,73 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local		5,58 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic		0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local		1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic		0,74 mg/kg bw/day

**PNEC values**

CAS No	Substance	Value
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg

**Additional advice on limit values**

To date, no national critical limit values exist.

**8.2. Exposure controls**

**MITANOL S-Force 15W-40 Classic**

Revision date: 09.02.2022

Page 5 of 10



**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

**Protective and hygiene measures**

Take off contaminated clothing and wash it before reuse.

Wash hands before breaks and after work.

When using do not eat, drink, smoke, sniff.

**Eye/face protection**

During filling, metering, mixing and sampling must be used:

Wear eye/face protection. DIN EN 166

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Recommended glove articles: EN ISO 374

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material: 0,4 mm

Breakthrough times and swelling properties of the material must be taken into consideration. Breakthrough time: > 8h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Wear suitable protective clothing.

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	clear
Odour:	characteristic
Odour threshold:	not determined

	Test method
pH-Value:	not determined
<b>Changes in the physical state</b>	
Melting point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Pour point:	-33 °C ASTM D 5985
Flash point:	245 °C ISO 2592
Sustaining combustion:	No data available
<b>Flammability</b>	
Solid/liquid:	not applicable
Gas:	not applicable

**Explosive properties**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

**MITANOL S-Force 15W-40 Classic**

Revision date: 09.02.2022

Page 6 of 10

Lower explosion limits:	not determined
Upper explosion limits:	not determined
Auto-ignition temperature:	No information available.
<b>Self-ignition temperature</b>	
Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined
<b>Oxidizing properties</b>	
The product is not: oxidising.	
Vapour pressure:	not determined
Vapour pressure:	No information available.
Density (at 15 °C):	0,8783 g/cm <sup>3</sup> DIN 51757
Water solubility:	Immiscible
<b>Solubility in other solvents</b>	
not determined	
Partition coefficient n-octanol/water:	not determined
Viscosity / dynamic:	not determined
Viscosity / kinematic: (at 40 °C)	105,6 mm <sup>2</sup> /s DIN EN ISO 3104
Flow time:	No information available.
Relative vapour density:	not determined
Evaporation rate:	not determined
Solvent separation test:	No information available.
Solvent content:	No information available.
<b><u>9.2. Other information</u></b>	
Solid content:	not determined

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

The formation of combustible vapours is possible at temperatures above: Flash point

**10.4. Conditions to avoid**

Avoid: Thermal decomposition

**10.5. Incompatible materials**

Materials to avoid:  
- Oxidising agent

**10.6. Hazardous decomposition products**

Hazardous combustion products:  
- Carbon monoxide (CO)  
- Carbon dioxide (CO<sub>2</sub>)  
- Nitrogen oxides (NO<sub>x</sub>)  
- Sulphur dioxide (SO<sub>2</sub>)  
- Phosphorus oxides

**MITANOL S-Force 15W-40 Classic**

Revision date: 09.02.2022

Page 7 of 10

- Pyrolysis products, toxic

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

The product contains less than 3% DMSO extract (method IP346). A classification as a carcinogen with R45 is deleted. (Note L)

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Additional information on tests**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

**11.2. Information on other hazards**

**Endocrine disrupting properties**

No information available.

**SECTION 12: Ecological information**

**12.1. Toxicity**

**MITANOL S-Force 15W-40 Classic**

Revision date: 09.02.2022

Page 8 of 10

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a

**12.2. Persistence and degradability**

The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

**12.3. Bioaccumulative potential**

No indication of bioaccumulation potential.

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

No information available.

**12.7. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

**Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number:**

No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:**

No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):**

No dangerous good in sense of this transport regulation.

**14.4. Packing group:**

No dangerous good in sense of this transport regulation.

**Inland waterways transport (ADN)**

**14.1. UN number:**

No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:**

No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):**

No dangerous good in sense of this transport regulation.



**MITANOL S-Force 15W-40 Classic**

Revision date: 09.02.2022

Page 9 of 10

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Marine transport (IMDG)**

**14.1. UN number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

No dangerous good in sense of this transport regulation.

**14.7. Maritime transport in bulk according to IMO instruments**

No dangerous good in sense of this transport regulation.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

**National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s):  
1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

**MITANOL S-Force 15W-40 Classic**

Revision date: 09.02.2022

Page 10 of 10

UN: United Nations  
DNEL: Derived No Effect Level  
DMEL: Derived Minimal Effect Level  
PNEC: Predicted No Effect Concentration  
ATE: Acute toxicity estimate  
LL50: Lethal loading, 50%  
EL50: Effect loading, 50%  
EC50: Effective Concentration 50%  
ErC50: Effective Concentration 50%, growth rate  
NOEC: No Observed Effect Concentration  
BCF: Bio-concentration factor  
PBT: persistent, bioaccumulative, toxic  
vPvB: very persistent, very bioaccumulative  
RID: Regulations concerning the international carriage of dangerous goods by rail  
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation  
intérieures)  
EmS: Emergency Schedules  
MFAG: Medical First Aid Guide  
ICAO: International Civil Aviation Organization  
MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
IBC: Intermediate Bulk Container  
SVHC: Substance of Very High Concern  
For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

**Relevant H and EUH statements (number and full text)**

H304                      May be fatal if swallowed and enters airways.

**Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*