

according to UK REACH Regulation

## **MITANOL X-Force 5W-30 RSI**

Revision date: 14.11.2022

Page 1 of 9

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

MITANOL X-Force 5W-30 RSI

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Motor oil multigrade

## Uses advised against

No information available.

#### 1.3. Details of the supplier of the safety data sheet

Company name:	MITANOL GmbH	
Street:	Industriestraße 8	
Place:	D-49577 Ankum	
Telephone:	+49 (0)5462/7470-50	Telefax: +49 (0)5462/7470-33
e-mail:	info@mitanol.de	
Internet:	www.mitanol.de	
Responsible Department:	Produktsicherheit / Product Safety	
	sicherheitsdatenblatt@mitanol.de	
1.4. Emergency telephone	Giftinformationszentrum Nord (Göttingen)	
<u>number:</u>	+49 (0)551/19240	

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### GB CLP Regulation

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

## 2.2. Label elements

#### Additional advice on labelling

According to EC directives or the corresponding national regulations the product does not have to be labelled.

## 2.3. Other hazards

No information available.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **Chemical characterization**

Preparation of base oils and additives.

#### Hazardous components

CAS No	Chemical name			Quantity		
	EC No Index No REACH No					
	GHS Classification	GHS Classification				
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	265-157-1	265-157-1 649-467-00-8 01-2119484627-25				
	Asp. Tox. 1; H304					

Full text of H and EUH statements: see section 16.



according to UK REACH Regulation

## MITANOL X-Force 5W-30 RSI

Revision date: 14.11.2022

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	c Chemical name			
	Specific Conc. Limits, M-factors and ATE				
64742-54-7	265-157-1 Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified		25 - 50 %		
inhalation: LC50 = 5,53 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg					

#### **Further Information**

This mixture contains no substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

Remove affected person from the danger area and lay down.

Do not leave affected person unattended.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### After inhalation

Remove person to fresh air and keep comfortable for breathing.

In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. In all cases of doubt, or when symptoms persist, seek medical advice.

## 4.2. Most important symptoms and effects, both acute and delayed

# No information available.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Use water spray jet to protect personnel and to cool endangered containers.

Co-ordinate fire-fighting measures to the fire surroundings.

- Water spray jet
- Carbon dioxide (CO2).
- Extinguishing powder

#### Unsuitable extinguishing media

High power water jet.

## 5.2. Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire. In case of fire may be liberated: Page 2 of 9



according to UK REACH Regulation

## **MITANOL X-Force 5W-30 RSI**

Revision date: 14.11.2022

- Carbon monoxide (CO)
- Carbon dioxide (CO2).
- Sulphur dioxide (SO2)
- Pyrolysis products, toxic

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Use of protective clothing

In case of fire and/or explosion do not breathe fumes.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### **General advice**

Keep people at a distance and stay on the windward side.

Special danger of slipping by leaking/spilling product.

## For non-emergency personnel

Wear protective gloves/protective clothing and eye/face protection.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Prevent spread over a wide area (e.g. by containment or oil barriers).

## 6.3. Methods and material for containment and cleaning up

#### For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation. Remove from the water surface (e.g. skimming, sucking).

## 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

Avoid formation of oil dust. Use personal protection equipment. Do not put any product-impregnated cleaning rags into your trouser pockets. Clear spills immediately.

## Advice on protection against fire and explosion

No special fire protection measures are necessary. Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place. Keep only in the original container. Store in a cool dry place. (Protect from moisture.) Floors should be impervious, resistant to liquids and easy to clean. Page 3 of 9



according to UK REACH Regulation

## **MITANOL X-Force 5W-30 RSI**

Revision date: 14.11.2022

Hints on joint storage

#### Do not store together with:

- Materials capable of ignition under almost all normal temperature conditions
- Explosives

#### Further information on storage conditions

Note Regulation on facilities for the storage, filling and handling water-polluting substances. ...

## 7.3. Specific end use(s)

Motor oil multigrade

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### DNEL/DMEL values

CAS No	Substance	_			
DNEL type		Exposure route	Effect	Value	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³	
Worker DNEL,	long-term	inhalation	local	5,58 mg/m³	
Worker DNEL,	long-term	dermal	systemic	0,97 mg/kg bw/day	
Consumer DNE	EL, long-term	inhalation	local	1,19 mg/m <sup>3</sup>	
Consumer DNE	EL, long-term	oral	systemic	0,74 mg/kg bw/day	

## **PNEC** values

CAS No	Substance		
Environmental compartment Value			
64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
Secondary poisoning 9,33 mg/kg			

#### Additional advice on limit values

To date, no national critical limit values exist.

## 8.2. Exposure controls





#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

## Protective and hygiene measures

Take off contaminated clothing and wash it before reuse.

Wash hands before breaks and after work.

When using do not eat, drink, smoke, sniff.

## Eye/face protection

During filling, metering, mixing and sampling must be used: Wear eye/face protection. EN 166

## Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the

Page 4 of 9



according to UK REACH Regulation

## **MITANOL X-Force 5W-30 RSI**

Revision date: 14.11.2022

Page 5 of 9

specific working place concentration and quantity of hazardous substances.

Recommended glove articles: EN ISO 374

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material: 0,4 mm

Breakthrough times and swelling properties of the material must be taken into consideration. Breakthrough time: > 8h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

## Skin protection

Wear suitable protective clothing.

## **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

## **SECTION 9: Physical and chemical properties**

## <u>9.1</u>

1. Information on basic physical and che	mical properties	
Physical state:	Liquid	
Colour:	brown	
Odour:	characteristic	
Odour threshold:	not determined	
		Test method
pH-Value:	not determined	
Changes in the physical state		
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	not determined	
Pour point:	-42 °C	ISO 3016
Flash point:	236 °C	DIN ISO 2592
Flammability		
Solid/liquid:	not applicable	
Gas:	not applicable	
Explosive properties The product is not: Explosive. Product are possible.	t is not explosive. However, formation of explosive air	/vapour mixtures
Lower explosion limits:	0,6 vol. %	
Upper explosion limits:	6,5 vol. %	
Auto-ignition temperature:	not determined	
Decomposition temperature:	not determined	
Oxidizing properties The product is not: oxidising.		
Vapour pressure:	not determined	
Density (at 20 °C):	0,852 g/cm³	DIN 51757
Water solubility:	Immiscible	
Solubility in other solvents not determined		
Partition coefficient n-octanol/water:	not determined	
Viscosity / kinematic: (at 40 °C)	72 mm²/s	DIN 51562



according to UK REACH Regulation

# MITANOL X-Force 5W-30 RSI Revision date: 14.11.2022

 Relative vapour density:
 not determined

 Evaporation rate:
 not determined

 9.2. Other information
 not determined

 Solid content:
 not determined

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

The formation of combustible vapours is possible at temperatures above: Flash point

#### 10.4. Conditions to avoid

Conditions to avoid: Thermal decomposition

#### 10.5. Incompatible materials

Materials to avoid:

- Oxidising agent, strong

## 10.6. Hazardous decomposition products

- Hazardous combustion products:
  - Carbon monoxide (CO)
  - Carbon dioxide (CO2).
  - Sulphur dioxide (SO2)
  - Pyrolysis products, toxic

## **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50	5,53 mg/l	Rat		OECD Guideline 403

## Irritation and corrosivity

Based on available data, the classification criteria are not met.

Frequently or prolonged contact with skin may cause dermal irritation.

#### Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

The product contains less than 3% DMSO extract (method IP346). A classification as a carcinogen with R45 is deleted. (Note L)

Page 6 of 9



according to UK REACH Regulation

## **MITANOL X-Force 5W-30 RSI**

Revision date: 14.11.2022

Page 7 of 9

## STOT-single exposure

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Additional information on tests

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

#### 11.2. Information on other hazards

Endocrine disrupting properties

See section: 12.6

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

The product spreads out on the surface of the water. A small fraction of the constituents will be dissolved. It prevents the solution of oxygen and can cause the death of water organismn.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified						
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas		OECD Guideline 203
	Fish toxicity	NOEC mg/l	>= 1000	14 d	, , ,	Brussels, Belgium	The aquatic toxicity was estimated by a

## 12.2. Persistence and degradability

Not readily biodegradable (according to OECD criteria)

#### 12.3. Bioaccumulative potential

Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

#### 12.4. Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

No information available.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

#### **Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

#### **SECTION 14: Transport information**



according to UK REACH Regulation

## MITANOL X-Force 5W-30 RSI

Revision date: 14.11.2022

Page 8 of 9

Land transport (ADR/RID)				
<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.			
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.			
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.			
14.4. Packing group:	No dangerous good in sense of this transport regulation.			
Inland waterways transport (ADN)				
<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.			
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.			
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.			
14.4. Packing group:	No dangerous good in sense of this transport regulation.			
Marine transport (IMDG)				
<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.			
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.			
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.			
14.4. Packing group:	No dangerous good in sense of this transport regulation.			
Air transport (ICAO-TI/IATA-DGR)				
<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.			
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.			
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.			
14.4. Packing group:	No dangerous good in sense of this transport regulation.			
14.5. Environmental hazards				
ENVIRONMENTALLY HAZARDOUS:	No			
14.6. Special precautions for user				
No dangerous good in sense of this tra	ansport regulation.			
14.7. Maritime transport in bulk according to	o IMO instruments			
No dangerous good in sense of this tra	ansport regulation.			
SECTION 15: Regulatory information				
15.1. Safety. health and environmental regu	lations/legislation specific for the substance or mixture			
EU regulatory information				
Information according to 2012/18/EU	Not subject to 2012/18/EU (SEVESO III)			
(SEVESO III):				
National regulatory information				
Water hazard class (D):	2 - obviously hazardous to water			
Additional information				
The product does not have to be labelled due to the calculation procedure of the "General Classification				

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

## 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

## Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,11,12,13,15,16.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route



## according to UK REACH Regulation

## **MITANOL X-Force 5W-30 RSI**

Revision date: 14.11.2022

Page 9 of 9

(European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50% CLP: Classification, labelling and Packaging REACH: Registration. Evaluation and Authorization of Chemicals GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals UN: United Nations DNEL: Derived No Effect Level DMFL: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50% EC50: Effective Concentration 50% ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration BCF: Bio-concentration factor PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative RID: Regulations concerning the international carriage of dangerous goods by rail ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) EmS: Emergency Schedules MFAG: Medical First Aid Guide ICAO: International Civil Aviation Organization MARPOL: International Convention for the Prevention of Marine Pollution from Ships IBC: Intermediate Bulk Container SVHC: Substance of Very High Concern For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

## Relevant H and EUH statements (number and full text)

May be fatal if swallowed and enters airways.

#### **Further Information**

H304

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)