

according to Regulation (EC) No 1907/2006

MITANOL X-Force 5W-40 Advance LA

Telefax: +49 (0)5462/7470-33

Print date: 17.02.2022

Revision date: 16.02.2022 Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

MITANOL X-Force 5W-40 Advance LA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Motor oil multigrade

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: MITANOL GmbH
Street: Industriestraße 8
Place: D-49577 Ankum
Telephone: +49 (0)5462/7470-50

e-mail: info@mitanol.de Internet: www.mitanol.de

Responsible Department: Produktsicherheit / Product Safety

sicherheitsdatenblatt@mitanol.de

1.4. Emergency telephone Giftinformationszentrum Nord (Göttingen)

number: +49 (0)551/19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

2.2. Label elements

Regulation (EC) No. 1272/2008

Special labelling of certain mixtures

EUH208 Contains Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an

allergic reaction.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation of base oils and additives.



according to Regulation (EC) No 1907/2006

MITANOL X-Force 5W-40 Advance LA

Revision date: 16.02.2022 Page 2 of 10

Hazardous components

CAS No	Chemical name			
	EC No	Index No	REACH No	
	GHS Classification			
68784-26-9	Phenol, dodecyl-, sulfurized, carbor	nates, calcium salts, overbased		0 - < 0,24 %
	272-234-3		01-2119524004-56	
	Repr. 1B, Aquatic Chronic 4; H360	H413		
148520-84-7	Benzene, mono-C10-13-alkyl derivs	s., fractionation bottoms, heavy ends	, sulfonated, calcium salts	0 - < 0,24 %
	800-941-4			
	Skin Sens. 1B; H317			
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts			0 - < 0,24 %
	274-263-7		01-2119492616-28	
	Skin Sens. 1B; H317			
68649-42-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts			0 - < 0,15 %
	272-028-3		01-2120742271-64	
	Skin Irrit. 2, Eye Irrit. 2, Aquatic Chronic 2; H315 H319 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
148520-84-7	800-941-4	Benzene, mono-C10-13-alkyl derivs., fractionation bottoms, heavy ends, sulfonated, calcium salts	0 - < 0,24 %
	Skin Sens. 1B;	H317: >= 10 - 100	
68649-42-3	272-028-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	0 - < 0,15 %
	dermal: LD50 =	: > 3160 mg/kg; oral: LD50 = 3100 mg/kg	

Further Information

This mixture contains no substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down.

Do not leave affected person unattended.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove person to fresh air and keep comfortable for breathing.

In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

Take off contaminated clothing and wash it before reuse.

In case of skin irritation, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.



according to Regulation (EC) No 1907/2006

MITANOL X-Force 5W-40 Advance LA

Revision date: 16.02.2022 Page 3 of 10

After ingestion

Rinse mouth thoroughly with water.

Let water be drunken in little sips (dilution effect).

Do NOT induce vomiting.

In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Use water spray jet to protect personnel and to cool endangered containers.

Co-ordinate fire-fighting measures to the fire surroundings.

- alcohol resistant foam
- Carbon dioxide (CO2).
- Extinguishing powder
- Water spray jet

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire may be liberated:

- Carbon monoxide (CO)
- Carbon dioxide (CO2).
- Nitrogen oxides (NOx)
- Pyrolysis products, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Use of protective clothing

In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Keep people at a distance and stay on the windward side.

Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Wear protective gloves/protective clothing and eye/face protection.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.



according to Regulation (EC) No 1907/2006

MITANOL X-Force 5W-40 Advance LA

Revision date: 16.02.2022 Page 4 of 10

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Remove from the water surface (e.g. skimming, sucking).

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of oil dust.

Use personal protection equipment.

Do not put any product-impregnated cleaning rags into your trouser pockets.

Clear spills immediately.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Take precautionary measures against static discharges.

Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

Keep only in the original container. Store in a cool dry place. (Protect from moisture.)

Floors should be impervious, resistant to liquids and easy to clean.

Hints on joint storage

Do not store together with:

- Materials capable of ignition under almost all normal temperature conditions
- Explosives

7.3. Specific end use(s)

Motor oil multigrade

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium s	salts		
Consumer , long-term inhalation		inhalation	systemic	11,75 mg/m³
Worker , long-term		dermal		3,33 mg/kg bw/day



according to Regulation (EC) No 1907/2006

MITANOL X-Force 5W-40 Advance LA

Revision date: 16.02.2022 Page 5 of 10

PNEC values

CAS No	Substance	
Environmenta	compartment	Value
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	
Freshwater 1 mg/l		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/kg
Secondary poisoning		16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse.

Wash hands before breaks and after work.

When using do not eat, drink, smoke, sniff.

Eve/face protection

During filling, metering, mixing and sampling must be used:

Wear eye/face protection. DIN EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Recommended glove articles: EN ISO 374 Suitable material: NBR (Nitrile rubber) Thickness of the glove material: 0.4 mm

Breakthrough times and swelling properties of the material must be taken into consideration. Breakthrough

time: > 8h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: yellow-brown
Odour: characteristic
Odour threshold: not determined

pH-Value: not determined



according to Regulation (EC) No 1907/2006

MITANOL X-Force 5W-40 Advance LA

Revision date: 16.02.2022 Page 6 of 10

Changes in the physical state

Melting point:

Boiling point or initial boiling point and

not determined

not determined

boiling range:

Pour point: -39 °C
Flash point: 234 °C

Flammability

Solid/liquid: not applicable
Gas: not applicable

Explosive properties

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Lower explosion limits:

not determined

Upper explosion limits: not determined

Self-ignition temperature

Solid: not applicable
Gas: not applicable
Decomposition temperature: not determined

Oxidizing properties

The product is not: oxidising.

Vapour pressure: not determined

Density (at 15,6 °C): 0,853 g/cm³

Water solubility: Immiscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Viscosity / dynamic:

viscosity / kinematic:

83 mm²/s

(at 40 °C)

Relative vapour density: not determined Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

The formation of combustible vapours is possible at temperatures above: Flash point

10.4. Conditions to avoid

Conditions to avoid: Thermal decomposition

10.5. Incompatible materials

Materials to avoid:

- Acids



according to Regulation (EC) No 1907/2006

MITANOL X-Force 5W-40 Advance LA

Revision date: 16.02.2022 Page 7 of 10

- Oxidising agent
- Reducing agent

10.6. Hazardous decomposition products

Hazardous combustion products:

- Carbon monoxide (CO)
- Carbon dioxide (CO2).
- Nitrogen oxides (NOx)
- Pyrolysis products, toxic

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
68649-42-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts					
	oral	LD50 31 mg/kg	100		Hazardous Substance DataBank [HSDB], U S	
	dermal	LD50 > 1 mg/kg	3160	Rabbit	United States Environmental Protection A	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

The product contains less than 3% DMSO extract (method IP346). A classification as a carcinogen with R45 is deleted. (Note L)

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential



according to Regulation (EC) No 1907/2006

MITANOL X-Force 5W-40 Advance LA

Revision date: 16.02.2022 Page 8 of 10

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68649-42-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	14,876

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land tran	sport	(ADR	(RID)
-----------	-------	------	-------

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4 Packing group:	No dangerous good in sense of this transport regulation

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No



according to Regulation (EC) No 1907/2006

MITANOL X-Force 5W-40 Advance LA

Revision date: 16.02.2022 Page 9 of 10

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Information according to 2012/18/EU

Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,11,12,15,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation

intérieures)

EmS: Emergency Schedules



according to Regulation (EC) No 1907/2006

MITANOL X-Force 5W-40 Advance LA

Revision date: 16.02.2022 Page 10 of 10

MFAG: Medical First Aid Guide

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

VOC: Volatile Organic Compounds

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
LISEO	May damage fortility or the unborn chi

H360 May damage fertility or the unborn child.
H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

EUH208 Contains Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an

allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)