

MITANOL MB 17

Low Viscosity HC-Synthetic Automatic Transmission Fluid

Properties

- excellent fuel economy
- excellent lubricity
- very high thermal stability
- high, stable viscosity index
- very good oxidation stability
- Protection against wear, corrosion and foam formation
- excellent cooling capacity
- excellent frictional stability

Application notes

- Especially for the latest Mercedes-Benz 9-speed automatic transmissions (9G-Tronic) 725.0 / 725.1 and 4MATIC
- **MITANOL MB 17** also meets the specifications of MB 236.16.
- **MITANOL MB 17 cannot** be used in older Mercedes-Benz automatic transmissions and is **not** downwards compatible with MB-Approval MB 236.10, MB 236.12, MB 236.14, MB 236.15

Observe manufacturer's instructions!

Service description

Recommendation*:

- MB 236.17

TYPICAL PARAMETERS	METHODS	UNITS	MITANOL MB 17
Thickness at 15°C	DIN EN ISO 12185	kg/m ³	846.3
Viscosity 40°C	DIN 51 562	mm ² /s	18.3
Viscosity 100°C	DIN 51 562	mm ² /s	4.3
Viscosity index (VI)	DIN ISO 2909	-	150
Pour point	ASTM D 7346	°C	-54
Flash point COC	DIN ISO 2592	°C	184
Colour	-	-	yellow brown

October 2020

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.