

MITANOL Monograde SAE 50

High-performance monograde engine oil

Properties

- High-performance monograde engine oil
- High viscosity index
- High dirt holding capacity
- Stable lubricant film
- Excellent cleaning power
- High thermal stability
- Excellent wear and corrosion protection

Application notes

MITANOL Monograde SAE 50 is suitable for use in diesel and gasoline engines with and without turbocharging, such as

- Commercial vehicle diesel engines
- Stationary diesel engines
- Construction machinery and agricultural aggregates

In addition, it is used in hydraulic systems, hydraulic clutches, transmissions, torque converters and retarders, if an appropriate engine oil is prescribed by the manufacturer.

Service description

Specifications:

- ACEA E2
- API SJ/CF-4

Recommendations*:

- MB 227.0
- MAN M 270
- Allison C-4
- Caterpillar TO-2
- MIL-L-2104 E
- MIL-L-46152 E
- MTU oil type 1

| TYPICAL PARAMETERS | METHODS | UNITS | MITANOL Monograde SAE 50 |
|----------------------|--------------|--------------------|--------------------------|
| Density at 15°C | DIN 51 757 | kg/m ³ | 899 |
| Viscosity 40°C | DIN 51 562 | mm ² /s | 239 |
| Viscosity 100°C | DIN 51 562 | mm ² /s | 19.5 |
| Viscosity index (VI) | DIN ISO 2909 | - | 93 |
| Pour point | DIN ISO 3016 | °C | -21 |
| Flash point COC | DIN ISO 2592 | °C | 290 |
| Base number | DIN ISO 3771 | mg KOH/g | 11.8 |
| Sulphated ash | DIN 51 575 | g/100 g | 1.6 |

October 2020

* meets the requirements of the OEM manufacturer.
 The stated values may vary within the usual commercial range.

MITAN Mineralöl GmbH

Industriestr. 8 • 49577 Ankum • Tel.: 05462/747050 • Fax: 05462/747033
 www.mitan-oil.de