

MITANOL TDL 80W-90

T.D.L - Transmission oil

Properties

MITANOL TDL 80W-90 is a HC-synthetic high-performance gear oil for universal use. Characterised by the following properties:

- Excellent thermal stability
- High viscosity index
- Very high shear stability
- Excellent corrosion protection
- Extension of oil change intervals
- Good driving comfort
- Increased wear protection

Application notes

MITANOL TDL 80W-90 is suitable for universal use in the complete Total Drive Line, consisting of synchronized and non-synchronized manual transmissions as well as axle and transfer cases in motor vehicles and commercial vehicles. In particular also for transmissions equipped with filter systems.

Not for manual transmissions with intarders!

Service description

Specifications:

- API GL-5
- API GL-4
- SAE J2360 (Mil-PRF-2105E)

Recommendations*:

- MB 235.0 / MB 235.6
- MAN 3343 Typ M,
- MAN 342 M1/M2
- MIL-L-2105D
- Scania STO 1:0
- Volvo 1273.21 / 1273.10
- ZF TE-ML 01, 05A, 07A, 08, 12A/E, 16B/C/D, 17B, 19B, 21A

TYPICAL PARAMETERS	METHODS	UNITS	MITANOL TDL 80W-90
Density at 15°C	DIN EN ISO 12185	kg/m ³	891
Viscosity 40°C	DIN 51 562	mm ² /s	167.5
Viscosity 100°C	DIN 51 562	mm ² /s	16.9
Viscosity index (VI)	DIN ISO 2909	-	107
Pour point	ASTM D 7346	°C	-30
Flash point COC	DIN ISO 2592	°C	204

* meets the requirements of the OEM manufacturer.
 The stated values may vary within the usual commercial range.