

## MITANOL X-Force 0W-40 Racing

High-performance low viscosity engine oil based on synthesis technology

### Properties

**MITANOL X-Force 0W-40 Racing** is a high-performance fuel-economy engine oil based on synthesis technology, for the highest performance requirements of supercharged and non-supercharged petrol and diesel engines in passenger cars. Outstanding flow properties guarantee excellent cold start behaviour. The exceptional high-temperature stability ensures a highly loadable lubricating film even under the most extreme conditions. Due to a high fuel saving **MITANOL X-Force 0W-40 Racing** contributes to the protection of the environment by reducing emissions.

### Application notes

**MITANOL X-Force 0W-40 Racing** is suitable as a top product for modern passenger car petrol and diesel engines, including the turbo versions.

### Service description

#### Specifications:

- ACEA A3/B4
- API SN/CF

#### Recommendation\*:

- BMW Longlife-01
- Ford WSS-M2C937-A
- MB 226.5 / MB 229.5
- Porsche A40
- Renault RN 0700 / RN 0710
- VW 502 00 / 505 00

TYPICAL PARAMETERS	METHODS	UNITS	MITANOL X-Force 0W-40 Racing
Density at 15°C	DIN 51 757	kg/m <sup>3</sup>	839
Viscosity at 40°C	DIN 51 562	mm <sup>2</sup> /s	74.2
Viscosity at 100°C	DIN 51 562	mm <sup>2</sup> /s	13.1
Viscosity Index (VI)	DIN ISO 2909	-	180
Viscosity at -35°C	DIN 51 377	mPa.s	6000
Pour point	DIN ISO 3016	°C	-42
Flash point COC	DIN ISO 2592	°C	230
TBN	DIN ISO 3771	mg KOH/g	12

\* meets the requirements of the OEM manufacturer.  
 The stated values may vary within the usual commercial range.